

Spectacular Signage Solution

FY-3200AT PLUS-E8



Standard printing delivered at production speed of 161 sqm/hr!


FEATURES




Industrial printhead with long life span and high productivity;



Specially enforced stainless steel for long-life strong and stable frame structure.



Waste ink collection system.



Double differential speed control design, auto smart tension bar, to ensure unattended printing to the very end of each media roll.



Ink detectors in main tank and waste ink tank.

Technical Specifications

Model	FY-3200AT PLUS-E8		
Printhead	Drop-on-demand piezo, 508 nozzles, 4 level gray scale		
Number of Printhead	8		
Print width	3200mm (125.98")		
Print Speed *	Draft	161m ² / h	
	Standard	121m ² / h	
	Quality	81m ² / h	
	High Quality	62m ² / h	
Media	Width	3300mm	
	Type	Banner, vinyl, mesh and other roll to roll outdoor printing material.	
Ink	Solvent ink, ECO solvent ink		
Ink supply system	Negative pressure ink supply		
Cleaning and Maintenance System	Individual positive pressure cleaning, manual one-piece capping, LED lamp at home position		
Heating System	Front, middle and back heater, IR dryer, fan cooling system		
RIP Software	United Fancy / Maintop / Photoprint		
Print Interface	Rj45		
Power Specification	Printer	AC220V	50HZ 5A 1100W
	Dryer	AC220V	50HZ 33A 7200W
	Platform heating	AC220V	50HZ 12A 2700W
Printer Dimension	L4992mm×W1105mm×H1649mm 1087KG		
Package Size	L5050mm×W1150mm×H1820mm 1367KG		

1. The speed data are taken from the printer at high speed, a difference of 10% may occur when running with different computers.
 2. Product specifications are subject to change without notice in advance. Color and shape in picture are for reference, computer and monitor not included. All rights reserved!